

**Wayne**  
FUELING SYSTEMS

WAYNE HELIX™ 6000 FUEL DISPENSER, EMEA



# Designed for the future

Popularity. It's what defines the Wayne Helix™ 6000 fuel dispenser. With unrivaled functionality, adaptability and capability, it's no surprise that this model is the favourite for fuel retailers across the globe.

The Helix 6000 fuel dispenser is engineered to perfectly adapt to any retail fuel site environment, no matter the size. Its minimal, contemporary design modernises forecourts, providing all of the features you need to deliver a seamless fuelling experience to your customers. It's got all of the functionality without the fuss.

## Wayne Helix 6000 fuel dispenser

### *Ultimate Scalability*

The Helix 6000 dispenser has the option to deliver up to five products, including alternative fuels, in a scalable framework that helps to optimise the dispenser size and layout for your forecourt. It is the only C-style model in the Helix range and is also available with an additive option, giving you the opportunity to increase your offer of premium grades.

Available Grades: 5 (blending available)
Available Nozzles: 5 per side
Available Flow Rates: 40, 70, 40-70 or 120 LPM
Hose Management: Simplified Hose Retraction (standard), Advanced Hose Retraction (optional)
Nozzle Reach: 3.5m (simplified retraction), 4m (advanced retraction)
Dispenser Orientation: Lane
Display Options: 6-7-5 (Volume – Price – Unit Price)
Vapour Recovery: Yes (unleaded only)
Automatic Temperature Compensation: Available as an option
Pump Type: CPU (Compact Pumping Unit) or remote
AdBlue® Configurations: Yes
LPG Configurations: Yes
Customised Livery: Yes
Corrosion Resistance: At least C3, stainless steel doors available for harsh environments
Operating Temperature: -40c to +55c
Relative Humidity: Condensing
Dimensions: Start at 1067 (L) x (600) H x (2050) (W) (vary depending on configuration)



For more information, please visit [wayne.com](http://wayne.com) or contact your regional sales representative.